

Domestic Salt-water Chlorination Systems



made in australia since 1980



The next generation in salt-water chlorinator for your home pool is now here. It is specifically designed for use on domestic pools ranging in size from 3,000 litres up to 300,000 litres. The NEW compact and light-weight control unit has been designed to operate with any salt concentration ranging from 3,000ppm up to 35,000ppm with variable chlorine output control. The NEW, highly efficient serial cell is automatic self-cleaning and made from the highest quality titanium electrodes.





The latest SALTMASTER is even EASIER to use. Simply press < or > to raise or lower the amount of chlorine you wish to produce.

Never add Chlorine again!

Take the health of your pool and your family into your own hands – it's that easy!



Chlorination Systems Technical Specification

MODEL		SM-15	SM-22	SM-33
TYPE		Domestic Salt-water Chlorination System		
SYSTEM PRODUCTION AND CONSUMPTION	Chlorine Production	15 grams/hour	22 grams/hour	33 grams/hr
	Power Consumption	180 Watts Maximum		
RECOMMENDED WATER CONDITIONING		<p>These systems utilize salt in the water to perform the sanitizing process but do not consume salt. Salt concentration can vary between 3,000 ppm and 35,000 ppm. These levels will only change when fresh water is added, for example, if it rains or, through backwashing the system. In either instance, salt should be added to regain the optimum concentration.</p> <p>Optimum conditions for user and operation require the following pool characteristics: Total Alkalinity 90-120ppm; pH 7.2-7.6; Chlorine Stabilizer (Isocynuric Acid) 50-80 ppm.</p>		
TYPICAL WATER TREATMENT CAPACITY	Cool Climate	<63,500 litres	<92,000 litres	<140,000 litres
	Hot Climate	<50,000 litres	<74,000 litres	<110,000 litres
POWER SUPPLY SPECIFICATION	Supply Specification	Primary Input: Voltage: 220-240 V AC Current: 10 Amps Max. (inc. pool pump supply) Secondary Output: Voltage: 28 V DC Current: 6.3 Amps Max. Total Power: 180 Watts Max.		
	Dimensions Power Supply: Cell Unit:	230mm x 200mm x 110mm 320mm (length) x 120mm (diameter)		
	Display and Controls	Chlorine Production rate: 10 LEDs; Polarity Display LED; No Flow Warning LED. Control Switches < and > to lower and raise production rate. Easy to program, manual flick switch 24 hour Timer: also to control circulation pump operation.		
CELL SPECIFICATION	Cell Material	High quality Coated Titanium electrodes		
	Plumbing	Cells are installed in-line in the plumbing situated on the return-to-pool line after the filter. All pipes, fittings and valves are industrial grade PVC or CPVC and have been tested to 500kPa. Cells are made from Acrylic for easy inspection.		
	Cell Cleaning	Self-cleaning, Reverse polarity cells.		
	Recommended Water Flow	Minimum Flow = 10 litres/second		
PROTECTION SYSTEMS		Primary Protection: - Current/Voltage Regulation; Circuit Breakers; Water flow cut-off detection system. Secondary Protection: - Constant Voltage Control; Current Limiting; Gas build-up avoidance via careful placement of unit along water return lines.		
MAINTENANCE		Periodic cell cleaning should be between 5-10 weeks, subject to local conditions; Cell Material is designed for 10,000 maximum-power operating hours. Refurbishment of cell can be done at a reduced cost.		
WARRANTIES		Wall mounted power supply – 3 years . Cells – 3 years* . *One year full warranty, two years pro-rata.		
APPROVALS		 		



AQUALINE
INTERNATIONAL

A Links Group Company LGT ME LLC

P.O. Box 73310 Dubai UAE
 Tel: +971 4 311 6535 Fax: +971 4 332 8810
 Email: cprucha@aqualineinternational.com

Aqualine International (Australia)
 Tel: +61 7 55949111 Fax: +61 7 55949266
 Email: aqualine@saltwatercapital.com.au

www.saltmaster.org